



TP-LINK

8-Port 10/100Mbps + 2-Port Gigabit Smart Switch

TL-SL2210

Overview

TP-LINK Smart Switch TL-SL2210 is equipped with 8 10/100Mbps RJ45 ports, 1 10/100/1000Mbps RJ45 ports and 1 SFP slot. This switch provides high performance, enterprise-level QoS, useful security strategies and rich layer 2 management features. TP-LINK smart switch TL-SL2210 is a cost-effective product solution for the small and medium business. TL-SL2210 has useful security features. The Storm Control feature protects against broadcast, multicast and unknown unicast storm. Quality of Service (QoS, L2 to L4) provides enhanced traffic management capabilities to move your data smoother and faster. Anymore, the easy-to-use web management interfaces, along with CLI, SNMP and RMON, mean faster setup and configuration with less downtime. For workgroup and departments requiring cost-sensitive layer 2 switch and gigabit capability, TP-LINK Smart Switch TL-SL2210 provides you the ideal access-edge solution.

Layer 2 Features

- Link Aggregation Control Protocol (LACP)
- Static Link Aggregation
- 64 VLANs
- Port Isolation
- STP/RSTP/MSTP
- IGMP Snooping

Quality of Service

- 4 priority queues
- Support IEEE 802.1P
- DSCP QoS
- Rate limit feature

Security Strategies

- Port Security
- Access Control List (L2~L4 ACL)
- Storm Control
- SSL and SSH encryptions
- DHCP Filtering

Management

- Web-based GUI
- Command Line Interface
- SNMP v1/v2c/v3
- RMON (1, 2, 3, 9 group)



TP-LINK
8-Port 10/100Mbps + 2-Port Gigabit
Smart Switch
TL-SL2210

Advanced QoS Features

To integrate voice, data and video service on one network, the switch applies rich QoS policies. Administrator can designate the priority of the traffic based on a variety of means including Port Priority, 802.1P Priority and DSCP Priority, to ensure that voice and video are always clear, smooth and jitter free.

Abundant Layer 2 features

For more applications of layer 2 switch, TL-SL2210 supports a complete lineup of layer 2 features, including 802.1Q tag VLAN, Port Isolation, Port Mirroring, STP/RSTP/MSTP, LACP and 802.3x Flow Control function. Any more, the switch provides advanced features for network maintenance, such as Loop Back Detection, Cable Diagnostics and IGMP Snooping. IGMP Snooping ensures the switch intelligently forward the multicast stream only to the appropriate subscribers while IGMP throttling & filtering restrict each subscriber on a port level to prevent unauthorized multicast access.

Enterprise Level Management Features


TL-SL2210 is easy to use and manage. It supports various user-friendly standard management features, such as intuitive web-based Graphical User Interface(GUI). SNMP (v1/v2c/v3) and RMON support enables the switch to be polled for valuable status information and send traps on abnormal events.



- Details:<http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included

Specifications

Hardware Features & Performance

| | | |
|------------------------|---|---|
| Product Picture |  | |
| Model | TL-SL2210 | |
| Physical Features | | |
| Connector | 10/100Mbps RJ45 Ports | 8 |
| | 10/100/1000Mbps RJ45 Ports | 1 |
| | Gigabit SFP Slots | 1 |
| Power Supply | 100-240VAC, 50/60Hz | |
| FAN Quantity | 0 | |
| Certifications | CE, FCC | |
| Dimensions (W × D × H) | 11.6 × 7.1 × 1.7 in. (290 × 180 × 44 mm), 13-inch Rackmount Steel Case, 1U Height | |
| Environment | Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing | |
| Performance | | |
| Switch Capacity | 5.6Gbps | |
| Forwarding Rate | 4.2Mpps | |
| MAC Address Table | 8k | |
| Package Buffer Memory | 4.1Mb | |
| Jumbo Frame | 10KB | |

Software Features

L2 Switching Features

- **Link Aggregation**
 - Support 802.3ad LACP
 - Support Static Link Aggregation
 - Up to 6 aggregation groups, containing 4 ports per group
- **Spanning Tree Protocol(STP)**
 - IEEE 802.1D Spanning Tree Protocol
 - IEEE 802.1W Rapid Spanning Tree Protocol
 - IEEE 802.1S Multiple Spanning Tree Protocol
 - STP Security: Loop back detection, TC Protect, BPDU Filter/Protect, Root Protect
- **Multicast**
 - Support IGMP Snooping v1/v2/v3, up to 256 groups
 - Support multicast VLANs, IGMP Immediate Leave, Unknown IGMP Throttling, IGMP Filtering, Static Multicast IP
- **VLAN**
 - Support IEEE802.1Q with 512 VLANs simultaneously (out of 4K VIDs)
- **IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode**

Quality of Service (QoS)

- Support 802.1p CoS/DSCP Priority
- Support 4 priority queues
- Queue scheduling: SP, WRR, SP+WRR
- Port/Flow-based rate limiting
- Voice VLAN assures voice applications much smoother performance

Advanced Security Strategies

- Support broadcast, multicast and unknown unicast Storm Control
- Static/Dynamic Port Security (MAC-based)
- Access Control List (ACL)-L2~L4 package filtering based on source and destination MAC address, IP address, TCP/UDP ports
- SSL and SSH encryptions

Management

- Support web-based GUI management mode
- Support Command Line Interface(CLI) through telnet management mode
- SNMP v1/v2c/v3
- RMON (1, 2, 3, 9 groups)
- DHCP/BOOTP Client
- CPU monitoring
- Port Mirroring (Many to One)

- Cable Diagnostics feature
- Ping/Tracert feature
- System log

Ethernet Protocols

- IEEE 802.3i 10BASE-T
- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3x Flow Control
- IEEE 802.1p QoS
- IEEE 802.1q VLANs / VLAN Tagging
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1W Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1S Multiple Spanning Tree Protocol (MSTP)

MIBs

- MIB II (RFC1213)
- Interface MIB (RFC2233)
- Ethernet Interface MIB (RFC1643)
- Bridge MIB (RFC1493)
- P/Q-Bridge MIB (RFC2674)
- RMON MIB (RFC2819)
- RMON2 MIB (RFC2021)
- Remote Ping, Traceroute MIB (RFC2925)
- Support TP-LINK private MIBs

Ordering Information

| Host Switch | |
|-----------------|---|
| Product Model | Description |
| TL-SL2210 | 8-Port 10/100Mbps + 2-Port Gigabit Smart Switch |
| Router | |
| Product Model | Description |
| TL-ER6120 | SafeStream Gigabit Dual-WAN VPN Router |
| TL-ER5120 | Gigabit Load Balance Broadband Router |
| SFP Modules | |
| Product Model | Description |
| TL-SM311LS | Gigabit SFP module, Single-mode, LC interface, up to 10km distance |
| TL-SM311LM | Gigabit SFP module, Multi-mode, LC interface, up to 550m distance |
| TL-SM321A | Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1550nm/RX:1310nm, 10km |
| TL-SM321B | Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1310nm/RX:1550nm, 10km |
| Media Converter | |
| Product Model | Description |
| MC210CS | Gigabit single-mode SC SFP Transceiver, up to 15Km, chassis mountable |
| MC200CM | Gigabit multi-mode SC SFP Transceiver, up to 550m, chassis mountable |
| MC220L | Gigabit SFP slot supporting mini-GBIC modules, chassis mountable |
| MC1400 | 14-slot power supply chassis for TP-LINK Media Converter, 19-inch rack-mountable |